



## **bibliotheca Tattle-Tape™ gate**

*superior security, seamless style*

This security system can blend nicely with your library décor while keeping your collection entirely secure using the latest DSP technology. Designed for use with Tattle-Tape™ Security Strips, this system detects all EM strips in any orientation. Along with a selection of built-in LED alarm light colours to choose from, it also features interchangeable graphic panels and is completely safe for all magnetic media.

# benefits of the Tattle-Tape™ gate

## reduce unwanted alarms

The Tattle-Tape™ gate can detect when an activated strip is leaving the library, significantly reducing false alarms at the gate when people enter. With multiple pedestals used to cover a larger entrance-way, the alarm lights on the gates also identify which aisle caused the alarm, helping staff locate items that triggered the alarm faster.

## integrated with libraryConnect™

Staff can remotely access libraryConnect™ for in-depth statistics and configuration options. This allows staff to remotely upgrade firmware, run monthly reports and change the alarm colours and patterns.

## genuine Tattle-Tape™ technology

With powerful algorithms, the genuine Tattle-Tape™ technology can distinguish between common metal items and any EM strip to yield the most accurate results. This means less false alarms and fewer inconveniences for both users and staff.

## superior detection of items in any orientation

Using the latest in DSP technology, the Tattle-Tape™ gate can detect EM strips regardless of the orientation within the gates, offering the highest level of detection, even in the noisiest of environments.

## integrated, visible people counter

The on-board bi-directional people counter accurately counts the number of people entering and leaving the library. This information is transferred to libraryConnect™ as well as the control box, which has a convenient display for quick access to live stats.

## selectable alarm colour and pattern

Both visual and audible security alarm settings are completely configurable by the library. With 8 LED colour alarms and patterns to choose from, the Tattle-Tape™ gate ensures both users and staff are alerted of items that have not been properly checked out.



## sleek design with interchangeable graphic sections

We designed our new Tattle-Tape™ gate to fit within new modern and updated library spaces. With easy-to-update panels, your security gates can match your library brand or promote an upcoming program.

## flexible configuration and installation

Simple set-up and maintenance allows our trained technicians to cause little disruption to your library and staff can quickly troubleshoot concerns with our dedicated phone support teams.

## Specifications : bibliotheca Tattle-Tape™ gate

<b>Dimensions (w x d x h):</b>	Millimetres: 51 (Max at base) x 597 x 1786 (± 3) Inches: 2.5 (Max at base) x 23.5 x 70.3 (± 0.1)
<b>Weight (per gate):</b>	Kilograms: 36.3 Pounds: 80
<b>Material:</b>	Pantone Cool Grey 4C HIPS
<b>Power:</b>	Supply voltage: 100/120, 220/240 VAC, 50 / 60 Hz Power consumption: 3.0A / 1.5A
<b>Data:</b>	Ethernet (TCP/IP)
<b>Performance:</b>	Optimised for detection of Tattle-Tape™ markers Optimal coverage is achieved within 39.4 inches / 1,000 mm of separation
<b>Alarm:</b>	Multi-colour*, customer selectable LED lights Variable alarm pattern and adjustable volume Highly visible integrated digital display to monitor alarm counts, ingoing and outgoing library user traffic, and diagnostics <small>*Available colours: red, cyan, magenta, blue, green, yellow, white, &amp; rotate mode</small>
<b>Standards compliance:</b>	CE, RCM, ETSI, FCC, IC, ADA, DDA, ETL and CSA
<b>Temperature range:</b>	Operating: 10 °C to +40 °C/Storage: -40 °C to +55 °C
<b>Configurations:</b>	Standard configuration can support up to 6 panels to provide total coverage of 6.0m
<b>Installation:</b>	Multiple installation options including direct attachment to the floor with either in floor wiring or a wire way and a baseplate option. The on-board tuning allows the gates to be placed within 45.7cm (18") from any metal objects, giving more freedom than ever to install within confined areas.
<b>Software:</b>	Software is not required for the Tattle-Tape™ gate to operate, however, when used in conjunction with our staffConnect™ gate software, enhanced reporting is available
<b>Additional features:</b>	Integrated bi-directional people counter. Ability to trigger external devices such as CCTV, voice alarms and entry gates.
<b>Options:</b>	Side panels can be customised to fit your libraries décor

Although we make every effort to ensure information is correct at the time of release, it is possible that specifications and features may vary or change over time. bibliotheca therefore makes no representations or warranties as to the completeness or accuracy of the information contained within this document.